5

10

15

20

25

CLAIMS .

47

1. Face detection apparatus generating an output indicative of the likelihood of test regions of a test image containing a face, the apparatus comprising:

means operable to compare a test region with face data indicative of the presence of a face in such a way as to detect plural respective likelihood values indicative of the likelihood of the test region containing a face of a group of respective different face sizes; and

control means, responsive to metadata associated with the image defining one of a set of predetermined classifications of the image, for modifying the group and/or the likelihood values in dependence upon a face size or range of face sizes appropriate to the classification of that image.

- 2. Apparatus according to claim 1, in the control means is operable to weight the likelihood values so as to enhance the detected likelihood of a face of a size appropriate to the classification of that image.
- 3. Apparatus according to claim 1, in which the control means is operable to select a subset of the group of different face sizes for the testing of the test region, the subset being dependent upon a face size or range of face sizes appropriate to the classification of that image.
- 4. Apparatus according to any one of the preceding claims, comprising means for detecting whether the likelihood value indicative of the greatest likelihood exceeds a threshold likelihood value.
- 5. Apparatus according to any one of the preceding claims, in which: the image is part of a video sequence; and the predetermined classifications include video programme types.
- 30 6. Apparatus according to any one of the preceding claims, in which the comparing means is operable:

to derive a set of attributes from respective blocks of the region;
to compare the derived attributes with attributes indicative of the presence of a face;
and

to derive a probability of the presence of a face by a similarity between the derived attributes and the attributes indicative of the presence of a face.

- 7. Apparatus according to claim 6, in which the attributes comprise the projections of image areas onto one or more image eigenblocks.
 - 8. Video conferencing apparatus comprising apparatus according to any one of the preceding claims.
- 9. Surveillance apparatus comprising apparatus according to any one of the preceding claims.
 - 10. Display apparatus comprising:
 - a display screen;
 - a video camera; and
 - apparatus according to any one of the preceding claims;

the video camera and the face detection apparatus being arranged with respect of the display screen so as to detect faces of those looking at the display screen.

20 11. A method of face detection apparatus for generating an output indicative of the likelihood of test regions of a test image containing a face, the method comprising the steps of:

comparing a test region with face data indicative of the presence of a face in such a way as to detect plural respective likelihood value indicative of the likelihood of the test region containing a face of a group of respective different face sizes; and

in response to metadata associated with the image defining one of a set of predetermined classifications of the image, modifying the group and/or the likelihood values in dependence upon a face size or range of face sizes appropriate to the classification of that image.

30

25

15

12. Computer software having program code for carrying out a method according to claim 11.

WO 2004/051553 PCT/GB2003/005236

- 13. A providing medium for providing program code according to claim 12.
- 14. A medium according to claim 13, the medium being a storage medium.
- 5 15. A medium according to claim 13, the medium being a transmission medium.

15

16. Face detection apparatus generating an output indicative of the likelihood of test regions of a test image containing a face, the apparatus comprising:

a comparator to compare a test region with face data indicative of the presence of a
face in such a way as to detect plural respective likelihood values indicative of the likelihood
of the test region containing a face of a group of respective different face sizes; and

a controller, responsive to metadata associated with the image defining one of a set of predetermined classifications of the image, to modify the group and/or the likelihood values in dependence upon a face size or range of face sizes appropriate to the classification of that image.